



AF2.90 WITH WORK TOP

Technical features

Reference values based on standard model.

FEATURE	AF2.90BAG	AF2.90BAV	AF2.90BG	AF2.90BV
Weight (indicative)	105 Kg / 231 lbs.	100 Kg / 220 lbs.	102 Kg / 225 lbs.	97 Kg / 214 lbs.
Machine dimension (Width x Depth x Height)	900x600x1000 mm / 35.4"x23.6"x39.4"			
Main water pressure	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min
Main steam pressure	-	0,15- 0,5 bar	-	0,15- 0,5 bar
Cold water connection • Connection • Min. and max temperature	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")
	5°C-20°C 41°F-68°F	5°C-20°C 41°F-68°F	5°C-20°C 41°F-68°F	5°C-20°C 41°F-68°F
Hot water connection • Connection • Min. and max temperature	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")
	45°C- 60°C 113°F- 140°F	45°C- 60°C 113°F- 140°F	45°C- 60°C 113°F- 140°F	45°C- 60°C 113°F- 140°F
Steam connection	-	Tube G 1/2" (BSPP 1/2")	-	Tube G 1/2" (BSPP 1/2")
Drain trap	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")
Working temperature	6°C- 40°C 42.8°F- 104°F	6°C- 40°C 42.8°F- 104°F	6°C- 40°C 42.8°F- 104°F	6°C- 40°C 42.8°F- 104°F
Max environment humidity	90%	90%	90%	90%



AT-OS SRL

Viale del Lavoro, 19- 37030 Colognola ai Colli - Verona - ITALY

Tel (+39) 045 6159411- Fax (+39) 045 6159422

info@at-os.com | www.at-os.com

