



AF2.45 COLUMN

Technical features

Reference values based on standard model.

FEATURE	AF2.45PEG	AF2.45PEV	AF2.45PG	AF2.45PV
Weight (indicative)	88 Kg / 194 lbs.	83 Kg / 183 lbs.	85 Kg / 187 lbs.	80 Kg / 176 lbs.
Machine dimension (Width x Depth x Height)	450x500x1500 mm / 17.7"x19.7"x 59.1"			
Main water pressure	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min	0,7- 6 bar 18 l/min
Main steam pressure	-	0,15- 0,5 bar	-	0,15- 0,5 bar
Cold water connection	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")
• Connection	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")
• Min. and max temperature	5°C- 20°C / 41°F- 68°F	5°C- 20°C / 41°F- 68°F	5°C- 20°C / 41°F- 68°F	5°C- 20°C / 41°F- 68°F
Hot water connection	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")	Male-thread G 3/4" (BSPP 3/4")
• Connection	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")	Tube G 1/2" (BSPP 1/2")
• Min. and max temperature	45°C- 60°C / 113°F- 140°F	45°C- 60°C / 113°F- 140°F	45°C- 60°C / 113°F- 140°F	45°C- 60°C / 113°F- 140°F
Steam connection	-	Tube G 1/2" (BSPP 1/2")	-	Tube G 1/2" (BSPP 1/2")
Drain trap	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")	Drain with hose barb connection Ø90 mm (3.54") + adapter included Ø110 mm (4.33")
Working temperature	6°C- 40°C / 42.8°F- 104°F	6°C- 40°C / 42.8°F- 104°F	6°C- 40°C / 42.8°F- 104°F	6°C- 40°C / 42.8°F- 104°F
Max environment humidity	90%	90%	90%	90%

*TECHNICAL FEATURES DATA ARE NOT AFFECTED BY PANEL MATERIAL



AT-OS SRL

Viale del Lavoro, 19- 37030 Colognola ai Colli - Verona - ITALY

Tel (+39) 045 6159411- Fax (+39) 045 6159422

info@at-os.com | www.at-os.com

