



AWD655-8L WITH SIDE PANEL

Technical features

Rated values based on standard model.

FEATURE	AWD655-8L AWD655-8XL AWD655-8XEL	AWD655-8L-SC
Weight (indicative)	115 Kg / 254 lbs.	120 Kg / 265 lbs.
Wash chamber dimension Width x Depth x Height	550x500x600 mm 21.7"x19.7"x23.6"	550x500x600 mm 21.7"x19.7"x23.6"
Wash chamber volume	165 l / 43.6 US gal	165 l / 43.6 US gal
Main water pressure	2- 5 bar 7 l/min	2- 5 bar 7 l/min
Cold water connection:		
• Connection	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")
• Min. and max temperature	5°C- 20°C / 41°F- 68°F	5°C- 20°C / 41°F- 68°F
• Max. water hardness	0.7 mmol/l CaCO ₃ / 3.9 °DH / 7°FH (without water softener)	0.7 mmol/l CaCO ₃ / 3.9 °DH / 7°FH (without water softener)
Hot water connection:		
• Connection	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")
• Min. and max temperature	45°C- 70°C / 113°F- 158°F	45°C- 70°C / 113°F- 158°F
• Max. water hardness	0.7 mmol/l CaCO ₃ / 3.9 °DH / 7°FH (without water softener)	0.7 mmol/l CaCO ₃ / 3.9 °DH / 7°FH (without water softener)
Deionized water connection:		
• Connection	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")	Male-thread G 3/4" (BSPP 3/4") Tube G 1/2" (BSPP 1/2")
• Min. and max temperature	5°C- 20°C / 41°F- 68°F	5°C- 20°C / 41°F- 68°F
• Max. water hardness	≤ 30 µS	≤ 30 µS
Drain trap (corrosion-proof and 93°C resistant pipe)	Drain DN40 (1.6") with hose barb connection Ø22 mm (0.9")	Drain DN40 (1.6") with hose barb connection Ø22 mm (0.9")
Min. and max working temperature	5°C- 40°C / 41°F- 104°F	5°C- 40°C / 41°F- 104°F
Max environment humidity	80%	80%
Max working altitude ASL (above sea level)	2000 m / 6562 ft	2000 m / 6562 ft



AT-OS SRL

Viale del Lavoro, 19- 37030 Colognola ai Colli - Verona - ITALY

Tel (+39) 045 6159411- Fax (+39) 045 6159422

info@at-os.com | www.at-os.com

